

1. Product

Maritime safety signs

2. Product Description

Self-adhesive plastic, 0.061mm thickness, antistatic surface and easy to clean.

3. Application

Remove any greasy content of the surface where the self-adhesive plastic is to be applied; remove the protector film of the adhesive; apply the product in the previously cleansed surface and press all the surface of the sign to fix it permanently.

More information in [Everlux](#) IMO catalogue, in chapter "Mounting Options".

4. Dimensions, Pictograms and Colours

The products are in conformity to [Everlux](#) catalogue and according to National and International Norms and Legislation.

5. Printing

Serigraphy: high quality gloss paint with UV resistance.

6. Cleanliness

The products do not require any particular attention, clean with a dry clean cloth or a cloth humidified with water (without detergents).

7. Guarantee

In normal conditions of mounting and adequate cleanness, the products have an indoor durability in excess of 5 years.

The type of surface where this product is applied (roughness and porosity levels, etc), its preparation for the adhesive (cleanness, to take away the fat, dust, etc), as well as the future conditions of cleanness may influence the durability and guarantee of the product.

For a maximum durability of the self adhesive maritime safety signs considerations has to be taken as the surface type and state on which it is to be placed, as the application temperature conditions.

For exterior applications, considering exposition to varying temperatures, humidity and other extreme environments, this guarantee can be diminished.

8. Health and safety

The product does not contain any radioactive substances. In toxic terms the product is considered as safe (European norm EN 71-3).

9. Quality and Certification

The quality of  Everlux[®] products is ensured by a rigorous process of quality control with tests in our own laboratory observing all applicable norms;

11. Legislation and Normative references


All of our signs are in conformity to the following norms:

- ISO 24409-1:2010
- ISO 7010:2011
- ISO 3864-1:2011
- ISO 3864-2:2004
- ISO 17631:2002
- ISO 15370: 2010
- ISO 14726:2008
- ISO 20712-1:2008

- BS 5499-1:2002
- BS 5499-1:2002
- BS 5499-11:2002

- IMO Resolution A.654 (16)
- IMO Resolution A.752 (18)
- IMO Resolution A.760 (18)
- IMO Resolution A.952 (23)
- Solas Convention 2004 chapter II-2 Reg. 13.3.2.5
- Solas Convention 2004 chapter II-2 Reg. 13.7.2.2
- Solas Convention 2004 chapter III-2 Reg. 9.2.3
- MARPOL 73/78 : 1978
- ISPS Code 2003
- ICAO and IMO document 9636
- IMDG Code 2010 Edition
- ISM Code 2010 Edition
- European Commission Directive 2002/25/EC

11. Specificities

The  Everlux[®] signs for external environments or wet environments with the presence of water with strong acid or alkaline content (eg limestone, salt and chlorine) should be protected by a transparent anti-graffiti film. This film, besides the anti-vandalism features, provides effective protection to environmental aggressions (pollution, humidity, UV radiation, chemicals ...).